

R3

Date of printing 13/4/2025

Technical data

NOTE: The photo shows a general example of the product.

| | |
|---------------------------------|-------------------|
| [MaximumMachineWeight] | 6000 - 12000 kg |
| [MaximumBucketWidth] | 1500 mm |
| [MaximumBreakingForce] | 81 kN |
| [MaximumBreakingTourque] | 85 kNm |
| [WeightFrom] | 300 kg |
| [TiltAngle] | 40° |
| [RotationSpeed] | 7.0 s at 50 l/min |
| [WorkingPreassure] | 25 MPa |
| [MinHydraulicFlow] | 69 l/min |
| [NrOfLubricationPoints] | 6 |
| [TurnTorque] | 6100 Nm at 25 MPa |
| [TiltTorqueA] | 21500 Nm |
| [TiltTorqueB] | 26500 Nm |



Measurement specification

| Dimension A, Width | Dimension B, Installation height total | Dimension C, Length | Dimension D, Installation height |
|---------------------------|---|----------------------------|---|
| 677 mm | 939 mm | 607 mm | 467 mm |

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

