Rototilt® Tiltrotators Page 1 of 1

RC9

Date of printing 3/31/2025

Technical data

NOTE: The photo shows a general example of the product.

Machine weight, max	70550 - 94800 lb	
Max standard bucket volume	81 cu ft	
Max bucket width	94 in	
Max breakout force	62945 lbf	
Max breakout torque	368780 ft.lb	
Weight (from)	3263 lb	
Tilt angle (2x)	40°	
Rotation speed (1 rotation per)	8.0 s at 33 gpm	
Working pressure	5076 psi	
Min hydraulic flow	54.42 gpm	
Recommended hydraulic flow	54 gpm	
Number of lubrication points	2	
Turning torque	14085 ft.lb at 3626 psi	
Tilt torque double acting cylinders	66380 ft.lb	



Dimensions

Dimension A, Width	Dimension B, Installation height total	Dimension C, Length	Dimension D, Installation height
53,66 in	62,28 in	45,83 in	30,43 in

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.



