

# R8

Date of printing 2025/04/02

## Technical data

NOTE: The photo shows a general example of the product.

|                          |                    |
|--------------------------|--------------------|
| [MaximumMachineWeight]   | 23000 - 32000 kg   |
| [MaximumBucketWidth]     | 2000 mm            |
| [MaximumBreakingForce]   | 200 kN             |
| [MaximumBreakingTourque] | 330 kNm            |
| [WeightFrom]             | 760 kg             |
| [TiltAngle]              | 40°                |
| [RotationSpeed]          | 8.0 s at 79 l/min  |
| [WorkingPreassure]       | 25 MPa             |
| [MinHydraulicFlow]       | 134 l/min          |
| [NrOfLubricationPoints]  | 6                  |
| [TurnTorque]             | 11940 Nm at 25 MPa |
| [TiltTorqueA]            | 50900 Nm           |
| [TiltTorqueB]            | 64700 Nm           |



## Measurement specification

| A,  | Dimension B, Installation height total | C,  | Dimension D, Installation height |
|-----|--|-----|----------------------------------|
| 948 | 1284 mm                                | 920 | 626 mm                           |
| mm  |  | mm  |                                  |

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

